



**Installation instructions**  
**Valve Control 2**  
**Hyundai i30N**

Remove parcel shelf and trunk floor:



Use a screwdriver to unscrew the plastic screws from the 3 marked clips and remove them. Then remove the loading sill cover completely:





Remove the clip on the passenger side of the sidewall cladding:



Unhook the screw covers with a small screwdriver and unscrew the screws underneath (nut 10mm):





Unscrew the 3 screws (10mm nut) and then remove the lower cover:



Now remove the cover for the rear shelf, note that the plug for trunk lighting and 12V socket must be unplugged:





Now pull the side panel forward and remove the standard rubber in the car body.  
Then pass the cable of the controller through the hole and insert the rubber of the controller.



Now remove the standard plug from the servomotor and connect it to the matching connector of the control system. Then connect the second connector of the control system with the servomotor:





Route the cable of the controller along the rear panel and then reassemble the passenger side in reverse order:



After you have reinstalled the loading sill cover, you can fix the control system under the cover with the attached velcro strips:



Here again the position of the control system in the overall view:



Then test, with the engine running, the control function.





Owner: Christian Müller  
Vorstadt 15  
94577 Winzer  
Germany

Phone: +49 (0) 9901 200981

Fax: +49 (0) 9901 200983

[www.special-exhaust.de](http://www.special-exhaust.de)

[info@special-exhaust.de](mailto:info@special-exhaust.de)